

*Requested Translation
5/15***PATENT ABSTRACTS OF JAPAN**

(11)Publication number : 61-026646
(43)Date of publication of application : 05.02.1986

(51)Int.Cl. C08L 51/04
C08L 69/00

(21)Application number : 59-145733 (71)Applicant : MITSUBISHI RAYON CO LTD
(22)Date of filing : 13.07.1984 (72)Inventor : TOYOOKA YUTAKA
KITAHARA HARUYOSHI

(54) THERMOPLASTIC RESIN COMPOSITION**(57)Abstract:**

PURPOSE: To obtain a composition giving a molded article having remarkably improved appearance and high impact resistance, by compounding a polycarbonate resin to an AAS resin prepared by using a specific crosslinked acrylic rubber having a multi-layered structure.

CONSTITUTION: The objective composition can be prepared by compounding (A) 5W95 (wt)% graft polymer obtained by the polymerization of 5W90pts.wt. of a mixture of (a) 10W90% aromatic vinyl compound and (b) 90W10% ethylenic unsaturated monomer of formula $\text{CH}_2=\text{CRX}$ (R is H or CH_3 ; X is CN or COOR₁; R₁ is 1W8C alkyl) in the presence of (c) a latex containing 100pts.wt. of a crosslinked acrylic rubber having multi-layered structure containing 5W50% crosslinked rigid resin having a particle diameter of 0.25W0.4 μ as a core, and 95W 50% crosslinked acrylic acid ester polymer constituting the outer layer of the multi-layered structure, (B) 5W95% polycarbonate resin and (C) 0W50% other rigid thermoplastic resin. The sum of the componensts A, B and C is 100%.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]